

## Klüberfluid 9 R 100

### Assembly and anticorrosion fluid

---

#### Benefits for your application

---

- **Compatible with SBR and EPDM elastomers \***
  - **Prevents corrosion during storage and transport**
  - **Miscible with brake fluids, e.g. in acc. with DOT 3, DOT 4 and DOT 5.1 \***
  - **Excellent wetting properties and high lubricity, especially when metal and elastomer materials are paired**
- 

#### Description

Klüberfluid 9 R 100 is a special synthetic oil based assembly fluid which can also be used as an efficient anticorrosion agent. Klüberfluid 9 R 100 is compatible with SBR and EPDM elastomers as well as with the brake fluids DOT 3, 4 and 5.1.\*

#### Application

Klüberfluid 9 R 100 is particularly suitable for automotive brake components. It can also be used as an anticorrosion agent for steel parts, protecting them while in stock and during transport between production and assembly, with the advantage that it does not have to be removed prior to the fitting of SBR and EPDM elastomer parts.

When used as an assembly fluid, Klüberfluid 9 R 100 facilitates the precise joining of individual components and thus supports functional reliability, preventing damage to the seals during fitting.

Klüberfluid 9 R 100 is used as an assembly aid, anticorrosion agent and functional lubricant, e.g. to attain the roll-back effect of brake pistons.

Its excellent wetting properties in conjunction with high lubricity have a favourable effect on initial friction, especially when metal and elastomer materials are paired.

#### Application notes

Due to its low viscosity, Klüberfluid 9 R 100 can be efficiently applied by immersion or spraying.

#### Minimum shelf life

The minimum shelf life is approximately 36 months if the product is stored in its unopened original container in a dry, frost-free place.

#### Pack sizes

1	x	20		canister
3	x	20		canister
10	x	20		canister
1	x	200		drum

#### Material Safety Data Sheets

Material safety data sheets can be downloaded or requested via our website [www.klueber.com](http://www.klueber.com). You may also obtain them through your contact person at Klüber Lubrication.



# Klüberfluid 9 R 100

## Assembly and anticorrosion fluid

Product data	Klüberfluid 9 R 100
Colour, aspect	red, clear
Density, DIN 51 757 at 20 °C [g/cm <sup>3</sup> ], approx.	0.96
Viscosity, DIN 51 562, part 01 at 40 °C, [mm <sup>2</sup> /s]	100 - 130
Flash point, DIN ISO 2592, [°C]	≥ 200

\* Owing to the many different elastomer compositions we recommend checking their compatibility on the complete component prior to series application

### Lubrication is our world

**With more than 2000 products available around the world, you can be sure that Klüber has the right product for your application. Please contact Klüber Lubrication specialists worldwide to assist you in all matters regarding lubrication.**

[www.klueber.com](http://www.klueber.com)

Klüber Lubrication München KG, Geisenhausenerstraße 7, 81379 München, Germany, phone +49 89 7876-0, fax +49 89 7876-333.

The data in this product information is based on our general experience and knowledge at the time of printing and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary tests with the selected product. We recommend contacting our Technical Consulting Staff to discuss your specific application. If required and possible we will be pleased to provide a sample for testing. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this product information at any time without notice.



Klüber Lubrication, a company of the Freudenberg Group

**Publisher and Copyright: Klüber Lubrication München KG.** Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München KG and if source is indicated and voucher copy is forwarded.

